

Patent Claims

1. A wall outlet, having a lower part with at least one first opening for holding an electrical cable and having a cover, with the cover or the lower part having at
5 least one second opening, into which an electrical socket can be inserted,
characterized in that
a routing element (21) is arranged in the lower part (20), by means of which the electrical cable (28) can be routed in a defined manner from the first opening (27) to the second opening (3).
- 10 2. The wall outlet as claimed in claim 1, characterized in that the routing element (21) is detachably connected to the lower part (20).
3. The wall outlet as claimed in claim 1 or 2, characterized in that the lower part
15 (20) has two first openings (27), and the cover (1) has two second openings (3).
4. The wall outlet as claimed in one of the preceding claims, characterized in that flaps (2) which can pivot are arranged on the cover (1) and can be used to close the second openings (3).
- 20 5. The wall outlet as claimed in claim 4, characterized in that the flap (2) has a latching trough, and the cover (1) has a latching tab.
6. The wall outlet as claimed in one of the preceding claims, characterized in that
25 hinge-like shafts (25) are arranged on both end surfaces (23, 24) on the lower part (20) and, on the end surface opposite the second opening (3), the cover (1) has attachment means (14) which correspond to the hinge-like shafts (25).
7. The wall outlet as claimed in one of the preceding claims, characterized in that
30 the routing element (21) has elements (35, 36) in the form of springs.
8. The wall outlet as claimed in one of the preceding claims, characterized in that the cover has lead-sealing hooks (6).

9. The wall outlet as claimed in one of the preceding claims, characterized in that a seal (11) is arranged between the lower part (20) and the cover (1).

5 10. The wall outlet as claimed in claim 9, characterized in that the holes (12) for attachment screws are arranged away from the seal (11).

10 11. The wall outlet as claimed in one of the preceding claims, characterized in that installation instructions (16) are fitted on the lower face of the cover (1) and/or on the upper face of the lower part (20).

12. The wall outlet as claimed in one of the preceding claims, characterized in that the cover (1) has a lid (8), and the lid (8) has a seal.

15 13. The wall outlet as claimed in one of the preceding claims, characterized in that at least one hinge-like shaft (25) is arranged on at least one end surface (23, 24) of the lower part (20), and the cover (1) has corresponding attachment means (14), with the hinge-like shaft (25) having a latching depression (39) and the corresponding attachment means (14) having a latching tab, so that the cover (1) latches in over a limiting angle when it is folded up.